

GREEN COUNTRY TRACTOR CLUB

TECHNICAL RULES

- 1. Div. II 1960 and older:** Tractors must have the factory block and head, frames, transmissions, rear end, and axle housing or the tractor manufactures replacement thru year 1960. No adapter plates allowed for engine, transmission, front end to bolt up. 10% over tractor stock rpm is allowed. No turbo chargers or blowers except factory installed. No alterations may be made to the frame or housings except for mounting weight brackets. Also must have factory wheel base. And maintain stock integrity of the class.
- 2. Div III and Open 1960 and older:** Tractors shall have factory appearing block and head. 20% over stock rpm allowed. No turbo chargers or blowers except factory installed. Div III must have stock wheel base. Open class may have any wheel base.
- 3. All tractors must be complete with no weight or fluids added after official weigh in “There is -0- allowance on weight for any class in any Division. Weight of class is maximum weight allowed, no exception.”**
- 4. Drawbar or hitch point shall not exceed 18” from ground level for Div II tractors. Div III and Open must not exceed 20” from ground level. Clevis height for all tractors will be measured from top of drawbar. Itch point shall be a max of 9” behind rear tires, and a minimum of 18” from center of rear axle. Drawbar cannot be less than 5/8 “ or more than 1 1/4” in depth and with, and must have a 3” x 2.5” opening. All drawbars must be in fixed position in all directions.**
- 5. Fuel Diesel fuel only in diesel tractors. Div II, III, and Open: No Nitro, Alcohol, or Nitro mixes allowed. No manually injected fuels or air in any engine.**
- 6. All tractors must have a working governor. “No Over-ride’s, No Alterations**
- 7. A Tractor may pull only once in each class, and must meet rules for the class. Drivers may drive only one tractor per class.**
- 8. Problems such as engine trouble, gas line plugging, jumping out of gear, and other problems, common to older tractors will not end the pull. Before unhooking from the sled the driver may request to re-pull. Granting of re-pull is the judge’s decision.**
- 9. Tires & Wheels: Div II Rear tractor rims may not be wider than tire size recommends. No radial tires. No hand altered, cut, intentionally altered, or dual wheels allowed. Div III and Open: No radial tires or duel wheels allowed. Any rim with and any cut on tire is allowed.**
- 10. All tractors must pass a safety/tech inspection prior to pulling. Stickers will be applied/displayed to indicate a passed inspection.**
- 11. Tractors pulling of exhibition purposes only, will pull at Superintendent’s discretion. Tractor must meet all safety rules.**
- 12. Wheelie bars are required on all tractors. Wheelie bars must be capable of holding the weight of the tractor in its heaviest class. Wheelie bars must extend behind rear tire. And must not be more than 10” above the ground. Wheelie bars will be checked by jacking them up one side at a time. Cross bars on wheelie bars must not contact the sled chain. Front weight brackets/weights may not extend more than 11 feet from center of rear axle.**

Chairman rules com. John Marney (Phone) Home 918-434-6754
Cell 918-530-8854